



## TRUST PRIMER SEALER

### WATER BASE PRIMER

- **USES**

For painting all interior & exterior wall. This product is generally applied on surfaces such as rendered concrete or plastered walls & sealings (plastered with putty) to strengthen the existing walls prior to be the application of any water base finishes; In addition, this product has excellent transpiration and covering power.

- **TECHNICAL CHARACTERISTICS**

**Composition:**

Based on vinyl acetate -ethylene-vinyl chloride terpolymer developed for emulsion paint manufacturer copolymer in aqueous emulsion, titanium dioxide carefully selected fillers and additives which give the product excellent filming characteristics, workability making the product highly resistant to light and alkali.

**Average specific weight:** About 1.54 kg/dm<sup>3</sup>

**Viscosity:** 20,000 - 25,000 cPs

**Solid content:** About 60% In weight

**Minimum film Forming temperature:** + 5°C

**Appearance of the film:** Mat

**Drying time:** About 1.5 - 3 hours at 20°C and 65% R.H.

**Tinting:** With basic Trust primer sealer colors in any proportion or by Trust colorimetric system according to the specifications of our Color Book, or by water based or universal type tinting pastes.

- **ADVISED**

**CONSUMPTION**

About 0.150 - 0.200 KG/M<sup>2</sup> (in two coats)

- **COLORS**

**AVAILABLE**

White

- **PACKINGS**

Drums of 25 kg & gallon of 5 kg each.

## Instructions for use

### • Surface Treatment of the substrate

**On new, thin rendered mortars:** a) Thinning primer sealer 1 : 1 with water

**On surfaces to be repainted:** a) Brush over the surface well  
b) Thinning primer sealer 1 : 1 with water

**On old plasters which are chalky, absorbent and degraded:** a) carefully remove all parts which are not securely anchored to the background and restore the surface where necessary.  
b) An undercoat of primer Enamel based thinned 1: 0.5 white spirit.

N.B. In every case however, before the application, the substrate should be dry, clean of any traces of grease or from -oils and any parts not perfectly anchored to the background.

### • Method of application

After an adequate preparation of the substrate, according to the above indications, apply the product by the brush or roller as follows:  
A first coat of Trust Primer Sealer thinned with about 75% of water

N.B. The product may also be applied by the spray even with airless type sprayer.

### • Storage

The product must be stored in well-closed drums, at temperatures not inferior to 0°C, protected from direct sunshine and strong heat.

### • WARNING AND SUGGESTIONS

Use only fresh, clean water for thinning and mix well before use. The ambient temperature for application is recommended to be between + 5°C and + 40°C.