



TRUST SEMI VINYL

Emulsion paint

- **USES**

For painting of all interior wall surfaces (but may also be used in certain application on exteriors where conditions are not severe). The applied product has excellent transpiration and covering power.
- **TECHNICAL CHARACTERISTICS**

Composition: Based on vinyl acetate -ethylene-vinyl chloride terpolymer developed for emulsion paint manufacturer copolymer in aqueous emulsion, titanium dioxide carefully selected fillers and additives which give the product excellent filming characteristics, workability making the product highly resistant to light and alkali.

Average specific weight: About 1.60 kg/dm³

Viscosity: 15,000 - 17,000 cPs

Solid content: About 65.50% In weight

Minimum film Forming temperature: + 5°C

Appearance of the film: Mat

Drying time: About 2 - 4 hours at 20°C and 65% R.H.

Tinting: With basic Trust SEMI VINYL colors in any proportion or by Trust colorimetric system according to the specifications of our Color Book, or by water based or universal type tinting pastes.
- **ADVISED CONSUMPTION**

About 0.200 - 0.250 KG/M² (in two coats)
- **COLORS AVAILABLE**

White, basic colors and any of the colors presented in our color guide.
- **PACKINGS**

Drums of 25 kg of 5 kg each.

Instructions for use

• Surface Treatment of the substrate

On new, thin rendered mortars: a) An undercoat of Trust SEMI VINYL thinned 1 : 1 with water

On surfaces to be repainted: a) Brush over the surface well
b) An undercoat of primer Enamel based thinned 1 : 0.5 white spirit.

On old plasters which are chalky, absorbent and degraded: a) carefully remove all parts which are not securely anchored to the background and restore the surface where necessary.
b) An undercoat of primer Enamel based thinned 1: 0.5 white spirit.

N.B. In every case however, before the application, the substrate should be dry, clean of any traces of grease or from -oils and any parts not perfectly anchored to the background.

• Method of application

After an adequate preparation of the substrate, according to the above indications, apply the product by the brush or roller as follows:

- a) A first coat of Trust SEMI VINYL thinned with about 40% of water
- b) A second coat of Trust SEMI VINYL thinned with about 25% of water

N.B. The product may also be applied by the spray even with airless type sprayer.

• Storage

The product must be stored in well-closed drums, at temperatures not inferior to 0°C, protected from direct sunshine and strong heat.

• WARNING AND SUGGESTIONS

Use only fresh, clean water for thinning and mix well before use. The ambient temperature for application is recommended to be between + 5°C and + 40°C.

The technical data and methods reported in this technical data sheet are subject to variations at any time according to the latest development in the production technology. The technical service of Trust is at the user disposal for the supply of integrative information to the herein reported.

