



# TRUST UNDERCOAT

## SOLVENT BASED PRIMER

### • USES

This product is used prior to paintings of all types of internal and external walls where a good adhesion of the finished product (whether it is solvent or water based ) finishes are required . In addition the normal performance of high quality undercoat primer one requires an outstanding resistance to wet abrasion. In addition it is ideal for painting prior to plaster, wallboard, wood or metal in kitchens, bathrooms, laundry rooms, halls.

### • TECHNICAL CHARACTERISTICS

**Composition:** Based on alkyd medium oil , and will not permit grease and hand smudges to adhere to its surface. Flows out to a smooth even film, free of brush marks and roller patterns and clings to sharp molding and trim edges. Titanium dioxide, carefully selected fillers and additives which give the product excellent filming characteristics, workability making the product highly resistant to light and alkali.

**Average specific weight:**

1. Pigment: 35%  
Titanium dioxide: 15%  
Silica: 8.5%
2. Vehicle: 40%  
Alkyd resin: 35%  
Volatile material: 18%

**Minimum film Forming temperature:** + 5°C

**Resistance to alkali:** Very good

**Washability:** 10,000 Gardner cycles

**Appearance of the film:** matt

**Drying time:** (temperature & humidity dependent).  
@77°F, 50%rh, 4.0 mils wet.  
Dust free 2-4 hours.  
Re-coat in 12 hours.  
Full cure 5 days.

### • ADVISED

#### CONSUMPTION

About 50 - 60M<sup>2</sup>/Gallon.

### • COLORS AVAILABLE

White, basic colors and any of the colors presented in our color guide.

### • PACKING

Drums of 20 Liter & USG

## Instructions for use

### • Surface treatment of the substrate

**On new, thin rendered mortars:** a) Brush and roller over the surface well.  
b) Thinning undercoat 50% white spirit.

**On surfaces to be repainted:** a) Brush and roller over the surface well  
b) An undercoat of primer “series 700” based thinned 50% white spirit

**On old plasters which are chalky, absorbent and degraded:** a) carefully remove all parts which are not securely anchored to the background and restore the surface where necessary.

N.B. In every case however, before the application, the substrate should be dry, clean of any traces of grease or from-oils and any parts not perfectly anchored to the background.

### • Method of application

After an adequate preparation of the substrate, according to the above indications, apply the product by the brush, or roller as follows:

One coat only required diluted with 50% white spirit

N.B. The product may also be applied by the spray even with airless type sprayer.

### • Storage

The product must be stored in well closed container, at temperatures not inferior to 0°C, protected from direct sunshine and strong heat.

### • Warnings and suggestions

Use only white spirit for thinning and mix well before use. The application should be carried out sheltered from direct sunshine, strong winds and rain. The ambient temperature for application is recommended to be between +5°C and +40°C. In addition it contains Aliphatic Hydrocarbons. Combustible, Keep away from heat open flame. Close container after each use. Protect from freezing. Use with adequate ventilation.