



## UNO VINYL MAT

High quality washable emulsion paint for interiors and exteriors

- **USES**

For painting of all types of internal as well as external wall where, in addition to the normal performance of good quality emulsion paint, one requires a highly washable finish.
- **Technical Characteristics**
  - Composition:**

Based on acrylated vinyl pressure polymer resins in aqueous emulsion, titanium dioxide, selected fillers and additives which give the product excellent filming characteristics, workability making the product highly resistant to light and alkali.
  - Average specific weight:** About 1.64 kg/dm<sup>3</sup>
  - Viscosity:** 13,000 - 15,000 cPs
  - Solid content:** About 65.50% In weight
  - Minimum film Forming temperature:** + 5°C
  - Appearance of the film:** Mat
  - Drying time:** About 2 - 4 hours at 20°C and 65% R.H.
  - Tinting:**

With basic Uno Vinyl Mat colors in any proportion or by rust colorimetric system according to the specifications of our Color Book, or by water based or universal type tinting pastes.
- **Advised Consumption**

About 0.200 - 0.250 KG/M<sup>2</sup> (in two coats)
- **Colors available**

White, basic colors and any of the colors presented in our color guide.
- **Packing**

Drums of 25 & USG.

## Instructions for use

- **Surface treatment of the substrate**

**On new, thin rendered mortars:** a) an undercoat of Uno Vinyl Mat thinned 1: 1 with water

**On surfaces to be repainted:** a) Brush over the surface well  
b) An undercoat of primer Enamel based thinned 1: 0.5 white spirit

**On old plasters which are chalky, absorbent and degraded:** a) carefully remove all parts which are not securely anchored to the background and restore the surface where necessary.

b) An undercoat of primer Enamel based thinned 1: 0.5 white spirit

N.B. In every case however, before the application, the substrate should be dry, clean of any traces of grease or from -oils and any parts not perfectly anchored to the background.

- **Method of application**

After an adequate preparation of the substrate, according to the above indications, apply the product by the brush or roller as follows:

- a) A first coat of Trust Vinyl Mat thinned with about 40% of water.
- b) A second coat of Trust Vinyl Mat thinned with about 25% of water.

N.B. The product may also be applied by the spray even with airless type sprayer.

- **Storage**

The product must be stored in well closed drums, at temperatures not inferior to 0°C, protected from direct sunshine and strong heat.

- **Warnings and suggestions**

Use only fresh, clean water for thinning and mix well before use. The application should be carried out sheltered from direct sunshine, strong winds and rain. The ambient temperature for application is recommended to be between + 5°C and + 40°C.